

LSI lineup for in-vehicle display systems


support of integrated HMI solution —

Advantage

- Modularizing the display can reduce the BOM and enables a single SoC to control the content
- High-performance 2D, 3D engine creates a vivid and impressive display system
- Cooperation with the authoring tool enables cluster designs in reduced time

Overview

Unlike traditional in-vehicle display systems, the Socionext solution does not use a controller for each display. Instead Socionext integrates its high-performance graphics SoCs and ancillary chipsets to create an integrated HMI solution that enables low-cost, simple configurations. The system frees the designer from previous development cycles, which make it difficult to apply increasingly complex content and image input / output. The designer can develop systems using a common process, irrespective of the target platform.



Note: APIX stands for **A**utomotive **Pix**el Link APIX is a Point-to-Point Video and Data Link optimized for Automotive environment provided by Inova Semiconductor, which is Headquartered in Munich, Germany.

Lineup

Graphic Display Controllers

	MB88F332	MB88F333	MB88F334
Package	LQFP 208	LQFP 176	LQFP 208
Processor	-	-	-
Display Controller	1×up to 1280×480 RGB666/RSDS	1×up to 1280×480 RGB666/RSDS	1×up to 1920×768 RGB/RSDS/LVDS
Graphics	Socionext Sprite Engine	Socionext Sprite Engine	Socionext Pixel Engine
Video	-	-	-
Memory	External Serial Flash I/F Embedded 160KB NOR-Flash	- Embedded 160KB NOR-Flash	External Serial Flash I/F Embedded 32KB NOR-Flash
Standard I/O	I2C Sound I/F UART SPI SMC PWM ADC	I2C Sound I/F UART SPI SMC PWM ADC	I2C Sound I/F UART SPI SMC PWM ADC
Network	-	-	e
APIX	APIX® RX 1port	APIX® RX 1port	APIX2® RX 1port

System On Chip

	MB86R11F	MB86R12	MB86R13	MB86R24
Package	PBBGA 544	TEBGA 544	TEBGA 544	FCBGA 672
Processor	Single ARM® Cortex™-A9 1×400MHz (Automotive)	Single ARM® Cortex [™] -A9 1×533MHz (Automotive)	Single ARM® Cortex [™] -A9 1×533MHz (Automotive)	Dual ARM® Cortex [™] -A9 2×533MHz (Automotive)
Display Controller	3×up to 1600×600@60Hz RGB/RSDS	3×up to 1600×600@60Hz RGB/RSDS	3×up to 1600×600@60Hz RGB/RSDS	2×up to 1920×720p 1×up tp 1920×1080p RGB/FPD
Graphics	Socionext 2D/3D Engine	Socionext 2D/3D Engine	Socionext 2D/3D Engine	Socionext 2D Engine POWERVR™ SGX543-MP1 3D Engine
Video	1×up to 1920×1080 3×up to 1280×720 Socionext Image Processor	1×up to 1920×1080 3×up to 1280×720 Socionext Image Processor	1×up to 1920×1080 3×up to 1280×720 Socionext Image Processor	6×up to 1920×1080 Socionext Image Processor
Memory	DDR2-800 DDR3-800/1066 ×16 ×32	DDR2-800 DDR3-800/1066 ×16 ×32	DDR2-800 DDR3-800/1066 ×16 ×32	DDR3/3L-1066 ×16 ×32 ×64
Standard I/O	I2C I2S UART SPI	I2C I2S UART SPI	I2C I2S UART SPI	I2C I2S UART SPI FPD-Link
Network	CAN Ethernet MOST (3-pin)	CAN Ethernet MOST (3-pin)	CAN Ethernet MOST (3-pin)	CAN Ethernet
APIX	-	APIX2® Tx 3port APIX2® Rx 1port	-	-

Companion Chip

	MB86R91	
Package	FBGA 289	
Automotive Interconnect	2× Automotive Interconnect (AIC) for connection to e.g. Socionext's MB9DF126 'Atlas' MCU	
Video	1× LVDS video input, configurable as follows: • 2× 4 lanes with up to 615 Mbps/lane (8 bit color) • 2× 3 lanes with up to 615 Mbps/lane (6 bit color) • 1× 8 lanes with up to 375 Mbps/lane (8 bit color) • 1× 6 lanes with up to 455 Mbps/lane (6 bit color) 1× Digital RGB888 video input 1× MIPI CSI2 transmitter (D-PHY 1.0), configurable 2 or 4 lanes 1× Media Independent Interface (MII-M) 1× Media Independent Interface (MII-P)	
APIX	APIX2® Tx 3port APIX2® Rx 1port	



For more information about our graphics SoC products, please visit http://www.socionext.com/en/products/imaging/gdc/

The Products and product specifications described in this document are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements. All company names, brand names and trademarks herein are property of their respective owners.

Copyright 2015 Socionext Inc.

AD04-00082-1E Nov. 2015

Edited: Graphics Solution Dept. IoT and Graphics Solution Business Unit

Socionext America, Inc.

1250 E. Arques Ave; MS 335 Sunnyvale, CA 94085 [408] 737-5400 | Toll free: [844] 680-3453 http://us.socionext.com SNA_inquiry@us.socionext.com