

# 8K Streaming Encoder "e8"




The 8K Streaming Encoder "e8" from Socionext generates live 8K video streams for expanding the use of high-quality video in a wide range of applications.

### **■**Features

- 8K60p real-time streaming of video shooting by 8K camera
- Easy to use and small body size (W:370mm × D:350mm × H:70mm)
- Offered with the Socionext 8K Media Player

#### [8K live streaming system]



### Applications

- Viewing of public live events
- Live streaming in commercial enterprises and organizations
- Real-time monitoring for medical applications
- 8K-VR streaming

## **■**Specifications

	Item	Specification
Interface	Input	<ul> <li>Connector: 12G-SDI x 4ch, DIN type</li> <li>Video: 8K, 2 sample interleave</li> <li>Audio: SDI embedded audio</li> </ul>
	Output	<ul><li>Gigabit Ethernet x 2ch</li><li>USB3.0 x 2ch (for recording)</li></ul>
Encoding Function	Video	<ul> <li>Resolution: 7680 x 4320 pixel</li> <li>Pixel format: 10bit, 8bit / 4:2:2, 4:2:0</li> <li>Framerate: 60, 59.94, 50, 30, 29.97, 25, 24, 23.98</li> <li>Encoding format: HEVC</li> <li>Bitrate: 60Mbps – 200Mbps</li> <li>Support embedding HDR parameters</li> </ul>
	Audio	<ul><li>Encoding format : AAC LC, Pass-through</li><li>Channel : 2ch</li></ul>
Streaming Function	Streaming Protocol	<ul> <li>HTTP Live Streaming (HLS)</li> <li>RTMP (with proprietary extension)</li> <li>RTP (with or w/o FEC)</li> <li>UDP</li> </ul>
	Container Format	- MPEG2-TS
Recoding Function	Supported Storage	- USB memory
	File Format	- MPEG4, MPEG2-TS, Video-ES
Chassis	User Interface	- Buttons and LCD display on front panel
	Dimensions	- 370mm (W) x 350mm (D) x 70mm (H)
	Power Supply	- 100 – 240V
Others	Certification	- CE - FCC Class A - CCC

<sup>\*</sup> This specification is subject to change without notice.